

WOC OEM OFFICIAL DX2 5W-30

07/05/2026
65607

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices

APPLICATIONS

This dexos 2™ approved oil is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2™ specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2™ lubricants.

FEATURES

Aftertreatment protection : full aftertreatment device protection.
Total engine protection : outstanding engine cleanliness and durability.
Fuel economy : lower fuel consumption and CO₂ emissions.

APPROVALS

GM dexos™2

SPECIFICATIONS

ACEA C2
ACEA C3
API SP
MB 229.51
MB 229.52
VW 505 00
VW 505 01

RECOMMENDATIONS

API CF
API SN
BMW LONGLIFE-04
CHRYSLER MS 11106
FIAT 9.55535-S3
FORD WSS-M2C917-A
GM dexos™1 Gen 3
GM dexos™D
HYUNDAI SFU
KIA SFU
MB 229.31
OPEL GM-LL-A-025
OPEL GM-LL-B-025
OPEL OV 040 1547 - D30
OPEL OV 040 1547 - G30
VW 502 00 < 2017

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium
Tel. +32 (0)3 870 00 00 - info@wocofficial.com

WWW.WOCOFFICIAL.COM

ENGINEERED BY
WOLF OIL
CORPORATION

WOC OEM OFFICIAL DX2 5W-30

07/05/2026
65607

TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	67.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.2
Viscosity index	ASTM D2270		182
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5400
Sulfated Ash	ASTM D874	Mass %	0.77
Flash Point COC	ASTM D92	°C	234

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium
Tel. +32 (0)3 870 00 00 - info@wocofficial.com

WWW.WOCOFFICIAL.COM

ENGINEERED BY
WOLF OIL
CORPORATION