

WOC OFFICIAL CLASSIC 15W-40

26/05/2026

This is a very high-quality mineral oil with proven performance. It has been upgraded to meet and exceed ACEA A3/B4. It is suitable for most 4-stroke gasoline and diesel cars as well as light trucks.

APPLICATIONS

4-stroke gasoline passenger cars engines (multi-valve, turbo, etc.); 4-stroke diesel engines, with or without turbo. High compatibility with biodiesel, based on extensive field trials.

FEATURES

Total engine protection: engine protection and cleanliness

RECOMMENDATION

ACEA A3/B3-16
ACEA A3/B4
API CF
API SN
FIAT 9.55535-D2
FIAT 9.55535-G2
MB 229.1
PSA B71 2295
RENAULT RN 0700
RENAULT RN 0710
VW 501 01
VW 505 00

TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.877
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	99.4
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270		140
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-33
Flash Point COC	ASTM D92	°C	218

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium
Tel. +32 (0)3 870 00 00 - info@wocofficial.com

WWW.WOCOFFICIAL.COM

ENGINEERED BY
WOLF OIL
CORPORATION