

WOC OEM OFFICIAL DX1 GEN3 5W-30

26/05/2026

Thanks to the low viscosity and excellent fluidity, this oil offers low wear, low emissions, and a strong fuel economy. Its carefully synthesized additive package targets soot and deposits to keep the engine clean. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This engine oil has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen 3 specification and ILSAC GF-7 A standard where fuel economy and CO₂ reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Cold start: excellent fluidity at low temperature

Fuel economy: excellent fuel economy and low exhaust emissions

Total engine protection: performance in keeping the engine clean

APPROVAL

GM dexos™1 Gen 3

SPECIFICATION

API SQ/RC

ILSAC GF-7 A

RECOMMENDATION

API SN

API SN Plus

API SN/RC

API SP

API SP/RC

API SQ

CHRYSLER MS 13340

CHRYSLER MS 6395

FIAT 9.55535-CR1

FORD WSS-M2C945-A

FORD WSS-M2C946-A

FORD WSS-M2C946-B1

FORD WSS-M2C947-A

FORD WSS-M2C961-A1

GM 4718M

GM 6094M

ILSAC GF-5

ILSAC GF-6 A

ILSAC GF-6A

VW VWC 53034

SUITED FOR USE:

GENESIS

HONDA

HYUNDAI

INFINITI

JAGUAR

KIA

LAND ROVER

LEXUS

MITSUBISHI

SUZUKI

TATA

TOYOTA

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium
Tel. +32 (0)3 870 00 00 - info@wocofficial.com

WWW.WOCOFFICIAL.COM

ENGINEERED BY
WOLF OIL
CORPORATION

WOC OEM OFFICIAL DX1 GEN3 5W-30

26/05/2026
16185

TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	63.4
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.0
Viscosity index	ASTM D2270		167
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium
Tel. +32 (0)3 870 00 00 - info@wocofficial.com

WWW.WOCOFFICIAL.COM

ENGINEERED BY
WOLF OIL
CORPORATION